

Description	Dimensions (W x H mm)	Cat Ref.
IP66 Wall Switches		

10AX 1 Gang 2 Way Switch	90 x 90	WXPPS12
10AX 2 Gang 2 Way Switch	90 x 90	WXPPS22
20AX Double Pole 1 Gang 1 Way Switch	90 x 90	WXDP84
10A1 Gang Bell Push Switch	90 x 90	WXPPS12B

IP66 Socket Outlets		
--------------------------------	--	--

13A 1 Gang Double Pole Unswitched Socket	103 x 116.5	WXPS81
13A 1 Gang Double Pole Switched Socket	103 x 116.5	WXPS81
13A 2 Gang Double Pole Unswitched Socket	164 x 116.5	WXPS82
13A 2 Gang Double Pole Switched Socket	164 x 116.5	WXPS82

IP66 Fused Connection Units		
--	--	--

13A Double Pole Fused Connect Unit with Flex Outlet	103 x 116.5	WXPSSU83FO
---	-------------	------------

:hager

Hager Ltd.
Unit M2
Furry Park Industrial Estate
Swords Road
Santry
Dublin D09 NY19
Ireland

Tel: 1890 551 502
Fax: 1890 551 503

hager.ie
customer.service@hager.ie
technical.service@hager.ie

 @HagerIreland

 @hagerireland

At A Glance

Sollysta
IP66



:hager

Our IP66 range is robust and durable solution for indoor or outdoor applications.



Moulded Plugs

Extended enclosure for extra wide gel seal mean even moulded on plugs can be accommodated.



Secure

A padlock of up to 5mm diameter shank can be fitted to the enclosure to prevent unauthorised use.



Soft Sealing

The factory fitted soft gel seal fits snugly around power cables to maintain the IP66 rating in use with the lid fully closed.



Protection

Manufactured from a tough, durable thermoplastic, the IP66 range is ideal for applications where wiring accessories may be vulnerable to the potentially harmful effects of dust and water ingress. The ip66 rating assures total protection.



180 Degrees

A unique dual action hinge allowing the lip to be opened a full 180 degrees for ease of plug insertion and switch operation.